

GREENTEK KONKRETE Primer

for the KONKRETE System.

PRODUCT DESCRIPTION:

Greentek KONKRETE Primer is a one component primer, with high penetrating powers specific for the **KONKRETE System**.

Greentek KONKRETE Primer reinforces the mineral surface of the **KONKRETE Top Coat** and optimizes the product performances of the Konkrete micro-cement during the application and hardening phases.

IDENTIFICATION FEATURES:

Density of the blend: 1.07 g/ml +/- 3%

PREPARATION OF THE SUBSTRATE

A grinder and vacuum machine is required.

PREPARATION OF THE PRODUCT

Greentek KONKRETE Primer is ready to use.

DILUTION:

No dilution needed.

WARNINGS:

During all stages of preparation of the support, products and applications, we recommend the proper use of equipment and personal protective equipment.

Do not expose the products for long periods in direct sources of heat or at temperatures below + 5 ° C. In the case of storage of the products at a temperature close to +5 ° C it is advisable to take them, before use, in place at the appropriate temperature, so as to be conditioned at a temperature of use not less than + 10 ° C. Do not heat the products using a direct source of heat, flame, hot body or the like.

Low temperatures increase the viscosity in the can making it difficult to use and lengthen or inhibit the process of drying and hardening of the various products.

It is advisable to complete each work with materials from the same production batch.

In the case of use of different batches, it is recommended to mix together the various productions.

CLEANING EQUIPMENT

With WATER.

Coverage:

5 to 8 m²/l per layer, depending on the required texture and on the substrate absorption.

COLORS:

Transparent.

PACKAGING

Primer one Component: 17 Ltrs.

STORAGE CONDITIONS AND SHELF LIFE:

The packaged products, if stored in its original and sealed package in a covered warehouse, at temperatures between +10 and 30°C, are guaranteed for 24 months.

